





1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name: K18 Cement White**
- **Application of the substance / the preparation** Adhesives
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Forbo Siegling Pty. Ltd
Factory 1, 124-126 Rodeo Drive
Dandenong South
Victoria 3175. Australia
Ph.: 1300137933
Fax: 1300137944
- **Information department:**
Chemical Laboratory
Email: Claudius.Hayduk@forbo.com
- **Emergency telephone number:**
(001) 352 323 3500 (Transport hazardous materials)
Poison emergency number Berlin 030-30686 790 (advice available in German and English)

2 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.


- **Dangerous components:**

CAS: 67-64-1 EINECS: 200-662-2	acetone	 Xi R36;  F R11 R66-67	25-50%
CAS: 78-93-3 EINECS: 201-159-0	Methylethylketon	 Xi R36;  F R11 R66-67	25-50%


- **Additional information** For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**

 Xi; Irritant

R36: Irritating to eyes.

 F; Highly flammable

R11: Highly flammable.

R66-67: Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Has a narcotizing effect.

- **Classification system:**

The classification was made according to the latest editions of the EU-lists, and expanded upon from company and literature data.

- **Label elements**

- **Labelling according to EU guidelines:**

The product has been marked in accordance with EU Directives / respective national laws.

- **Code letter and hazard designation of product:**



Xi Irritant
F Highly flammable

Safety data sheet

According to 91/155 EEC

Printing date 01.11.2012

Version number 8

Revision: 01.11.2012

Trade name: K18 Cement White

(Contd. of page 1)

· Risk phrases:

- 11 Highly flammable.
- 36 Irritating to eyes.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

· Information pertaining to particular dangers for man and environment
· Safety phrases:

- 9 Keep container in a well-ventilated place.
- 16 Keep away from sources of ignition - No smoking.
- 23 Do not breathe vapour.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 29 Do not empty into drains.
- 60 This material and its container must be disposed of as hazardous waste.

4 First aid measures

- **After inhalation** Supply fresh air; consult doctor in case of complaints.
- **After skin contact** Generally the product does not irritate the skin.
- **After eye contact**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing** If symptoms persist consult doctor.
- **Information for doctor** MSDB

5 Firefighting measures

- **Suitable extinguishing agents**
Alcohol resistant foam



CO₂, sand, extinguishing powder. Do not use water.

- **For safety reasons unsuitable extinguishing agents**
Water.
Water with full jet.
- **Special hazards arising from the substance or mixture**
In case of fire, the following can be released:
Carbon monoxide (CO)
Nitrogen oxides (NO_x)
In certain fire conditions, traces of other toxic gases cannot be excluded.
- **Protective equipment:** Wear self-contained respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Keep away from ignition sources
Keep people at a distance and stay on the windward side.
Use respiratory protective device against the effects of fumes/dust/aerosol.



Wear protective equipment. Keep unprotected persons away.

- **Environmental precautions:**
Prevent seepage into sewage system, workpits and cellars.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.

(Contd. on page 3)

Safety data sheet

According to 91/155 EEC

Printing date 01.11.2012

Version number 8

Revision: 01.11.2012

Trade name: K18 Cement White

See Section 13 for disposal information.

(Contd. of page 2)

7 Handling and storage

- **Handling**

- **Precautions for safe handling**

Store in cool, dry place in tightly closed receptacles.

Carry out filling operations only at sites with extractors available.

Wear suitable respiratory protective device when decanting larger quantities without extractor facilities.

Use solvent-proof equipment.

Ensure good ventilation/exhaustion at the workplace.

- **Information about protection against explosions and fires:**

Highly volatile, flammable constituents are released during processing.

Wear shoes with conductive soles.

Use only in explosion protected area.

Use explosion-proof apparatus / fittings and spark-proof tools.



Keep ignition sources away - Do not smoke.

- **Storage**

- **Requirements to be met by storerooms and receptacles:**

Provide solvent resistant, sealed floor.

Prevent any seepage into the ground.

Use only receptacles specifically permitted for this substance/product.

Store in a cool location.

- **Information about storage in one common storage facility:** Store away from oxidizing agents.

- **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- **Storage class 3**

- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Components with limit values that require monitoring at the workplace:**

67-64-1 acetone	
NES (Australia)	Short-term value: 2375 mg/m ³ , 1000 ppm Long-term value: 1185 mg/m ³ , 500 ppm
78-93-3 Methylethylketon	
NES (Australia)	Short-term value: 890 mg/m ³ , 300 ppm Long-term value: 445 mg/m ³ , 150 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Personal protective equipment**

- **General protective and hygienic measures**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- **Breathing equipment:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**

Solvent resistant gloves

After use of gloves apply skin-cleaning agents and skin cosmetics.

(Contd. on page 4)

AU

Safety data sheet

According to 91/155 EEC

Printing date 01.11.2012

Version number 8

Revision: 01.11.2012

Trade name: K18 Cement White

(Contd. of page 3)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

- Butyl rubber, BR

- The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Natural rubber, NR

- **Penetration time of glove material**

- The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:** Safety glasses

- **Body protection:** Protective work clothing.

9 Physical and chemical properties

- **General Information**

- **Appearance:**

Form:	Fluid
Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.

- **pH-value:** Not determined.

- **Change in condition**

- Boiling point/Boiling range:** 55°C

- **Flash point:** -15°C

- **Flammability (solid, gaseous)** Not applicable.

- **Ignition temperature:** 340°C

- **Decomposition temperature:** Not determined.

- **Self igniting** Not determined.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

- **Explosion limits:**

Lower:	1.8 Vol %
Upper:	13.0 Vol %

- **Vapour pressure at 20°C:** 247 hPa

· Density at 20°C:	0.99 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.

- **Solubility in / Miscibility with**

- Water:** Not miscible or difficult to mix

- **Partition coefficient (n-octanol/water):** Not determined.

- **Viscosity:**

dynamic:	Not determined.
kinematic:	Not determined.

- **Solvent content:**

- Organic solvents:** 77.3 %

- Solids content:** 22.7 %

- **Other information** No further relevant information available.

AU

(Contd. on page 5)

Safety data sheet

According to 91/155 EEC

Printing date 01.11.2012

Version number 8

Revision: 01.11.2012

Trade name: K18 Cement White

(Contd. of page 4)

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known

11 Toxicological information

- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant

12 Ecological information

- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**



Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**

08 04 09*	waste adhesives and sealants containing organic solvents or other dangerous substances
-----------	--

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|----------------------------------|--|
| · UN-Number | |
| · ADR, IMDG, IATA | UN1133 |
| · UN proper shipping name | |
| · ADR | 1133 ADHESIVES, special provision 640D |
| · IMDG, IATA | ADHESIVES |

- **Transport hazard class(es)**
- **ADR, IMDG, IATA**



- **Class** 3 Flammable liquids.

(Contd. on page 6)

-AU

Safety data sheet

According to 91/155 EEC

Printing date 01.11.2012

Version number 8

Revision: 01.11.2012

Trade name: K18 Cement White

(Contd. of page 5)

· Label	3
· Packing group	II
· ADR, IMDG, IATA	
· Environmental hazards:	No
· Marine pollutant:	
· Special precautions for user	Warning: Flammable liquids.
· Danger code (Kemler):	33
· EMS Number:	F-E,S-D
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	D/E
· Tunnel restriction code	

15 Regulatory information

· **Australian Inventory of Chemical Substances**

All ingredients are listed.

· **Standard for the Uniform Scheduling of Drugs and Poisons**

67-64-1	acetone	S5
78-93-3	Methylethylketon	S5

· **Markings according to EU guidelines:**

The product has been marked in accordance with EU Directives / respective national laws.

· **Code letter and hazard designation of product:**



Xi Irritant
F Highly flammable

· **Risk phrases:**

- 11 Highly flammable.
- 36 Irritating to eyes.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

· **Safety phrases:**

- 9 Keep container in a well-ventilated place.
- 16 Keep away from sources of ignition - No smoking.
- 23 Do not breathe vapour.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 29 Do not empty into drains.
- 60 This material and its container must be disposed of as hazardous waste.

· **National regulations**

· **Technical instructions (air):**

Class	Share in %
II	35.2
NK	43.0

· **Water hazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- R11 Highly flammable.
- R36 Irritating to eyes.

(Contd. on page 7)

Safety data sheet
According to 91/155 EEC

Printing date 01.11.2012

Version number 8

Revision: 01.11.2012

Trade name: K18 Cement White

(Contd. of page 6)

R66 Repeated exposure may cause skin dryness or cracking.
R67 Vapours may cause drowsiness and dizziness.

· **Department issuing MSDS:** Chemical Laboratory

· **Contact:**

C.Hayduk

Tel.-Nr. +49 511 6704 214

Fax-Nr. +49 511 6704 489

Mobil-Nr.+49 151 11741970

· * **Data compared to the previous version altered.**

-AU-