



SAFETY DATA SHEET

Section 1: IDENTIFICATION

1.1 PRODUCT IDENTIFIER

Product Name: Complete Contact RS Mortar (White & Gray)
Product Code: N/A

1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

Use: Mortar.

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Name/Address: Custom Building Products
13001 Seal Beach Blvd
Seal Beach, CA 90740

Telephone Number: (562) 598-8808

1.4 EMERGENCY TELEPHONE NUMBER

Emergency Telephone Number: INFOTRAC 1-800-535-5053 (US and Canada)
INTERNATIONAL + 1-352-323-3500

Section 2: HAZARD(S) IDENTIFICATION

2.1 CLASSIFICATION OF THE CHEMICAL ACCORDING TO OSHA HAZCOM 2012

Hazard class

Skin irritation 2
Serious eye damage 1
Skin sensitization 1
Carcinogenicity 1A
Reproductive Toxicity 1B
Specific target organ toxicity - Single exposure 3
Specific target organ toxicity - Repeated exposure 1

2.2 LABEL ELEMENTS ACCORDING TO OSHA HAZCOM 2012

Hazard Pictogram:



Signal Word: Danger

Hazard Statement: Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. May cause cancer. May damage fertility or the unborn child. May cause respiratory irritation. Causes damage to lungs through prolonged or repeated exposure.

Prevention: Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. Do not breathe dust. Do not eat, drink or smoke when using this product.



SAFETY DATA SHEET

Response:	If exposed or concerned: Get medical advice/attention. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.
Storage:	Store locked up. Store in a well-ventilated place. Keep container tightly closed.
Disposal:	Dispose of contents and container in accordance with all local, regional, national and international regulations.

2.3 ADDITIONAL INFORMATION

Hazards not otherwise classified: Not applicable.

33 % of the mixture consists of ingredient(s) of unknown acute toxicity.

WHMIS Classification(s):

- Class D2A - Carcinogenicity
- Class D2A - Chronic Toxic Effects
- Class D2B - Skin/Eye Irritant

WHMIS Hazard Symbols:



WHMIS Signal Word: WARNING

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 MIXTURES

Ingredient	CAS No	Wt. %
Silica, crystalline, quartz	14808-60-7	40 - 70
Portland cement	65997-15-1	10 - 30
Cement, alumina, chemicals	65997-16-2	7 - 13
Calcium sulfate	7778-18-9	1 - 5
Gypsum	13397-24-5	0.5 - 1.5*
Calcium carbonate	1317-65-3	0.5 - 1.5
Kaolin	1332-58-7	0.1 - 1
Lithium carbonate	554-13-2	0.1 - 1

*Complete Contact RS Mortar - White

The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.



SAFETY DATA SHEET

Section 4: FIRST- AID MEASURES

4.1 DESCRIPTION OF THE FIRST AID MEASURE

- Eye:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.
- Skin:** In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
- Inhalation:** If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
- Ingestion:** If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

- Eye:** Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns in the presence of moisture.
- Skin:** Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. May cause sensitization by skin contact.
- Inhalation:** May cause respiratory tract irritation.
- Ingestion:** May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENTS NEEDED

- Note to Physicians:** Symptoms may not appear immediately.
- Specific Treatments:** In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

Section 5: FIRE-FIGHTING MEASURES

5.1 FLAMMABILITY

- Flammability:** Not flammable by WHMIS/OSHA criteria.

5.2 EXTINGUISHING MEDIA

- Suitable Extinguishing Media:** Treat for surrounding material.
- Unsuitable Extinguishing Media:** Not available.



SAFETY DATA SHEET

5.3 SPECIAL HAZARDS ARISING FROM THE CHEMICAL

Products of Combustion: May include, and are not limited to: oxides of carbon.

Explosion Data:

Sensitivity to Mechanical Impact: Not available.

Sensitivity to Static Discharge: Not available.

5.4 SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS

Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING - UP

Methods for Containment: Pick up large pieces, then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for Cleaning-Up: Vacuum or sweep material and place in a disposal container.

Section 7: HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING

Handling: Avoid contact with skin and eyes. Do not swallow. Do not breathe dust. Good housekeeping is important to prevent accumulation of dust. Avoid generating dust. The use of compressed air for cleaning clothing, equipment, etc, is not recommended. Use only in well-ventilated areas. Handle and open container with care. When using do not eat or drink. (See section 8)

General Hygiene Advice: Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage: Keep out of the reach of children. Store in dust-tight, dry, labeled containers. Keep containers closed when not in use. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area. Do not store in an area equipped with emergency water sprinklers. Use corrosion-resistant structural materials and lighting and ventilation systems in the storage area. (See section 10)



SAFETY DATA SHEET

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS

Exposure Guidelines

Ingredient	Occupational Exposure Limits	
	OSHA-PEL	ACGIH-TLV
Silica, crystalline, quartz	((10 mg/m ³)/(%SiO ₂ +2) TWA (resp)) ((30 mg/m ³)/(%SiO ₂ +2) TWA (total)) ((250)/(%SiO ₂ +5) mppcf TWA (resp))	0.025 mg/m ³
Portland cement	15 mg/m ³ (total); 5 mg/m ³ (resp)	1 mg/m ³ (no asbestos and <1% crystalline silica, respirable fraction)
Cement, alumina, chemicals	Not available.	Not available.
Calcium sulfate	15 mg/m ³ TWA (total dust) 5 mg/m ³ TWA (respirable fraction)	10 mg/m ³
Gypsum	15 mg/m ³ TWA (total dust) 5 mg/m ³ TWA (respirable fraction)	10 mg/m ³
Calcium carbonate	15 mg/m ³ (total); 5 mg/m ³ (resp)	10 mg/m ³
Kaolin	15 mg/m ³	2 mg/m ³
Lithium carbonate	Not available.	Not available.

8.2 EXPOSURE CONTROLS

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

8.3 INDIVIDUAL PROTECTIVE MEASURES

Personal Protective Equipment:

Eye/Face Protection: Wear approved eye (properly fitted dust- or splash-proof chemical safety goggles) / face (face shield) protection.

Skin Protection:

Hand Protection: Wear suitable gloves.

Body Protection: Wear suitable protective clothing.

Respiratory Protection: A NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).

General Health and Safety Measures: Handle according to established industrial hygiene and safety practices.



SAFETY DATA SHEET

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Powder.
Color:	White/Gray.
Odor:	Characteristic.
Odor Threshold:	Not available.
Physical State:	Solid.
pH:	~11.8
Melting Point/Freezing Point:	Not available.
Initial Boiling Point and Boiling Range:	Not available.
Flash Point:	Not available.
Evaporation Rate:	Not available.
Flammability:	Not flammable.
Lower Flammability/Explosive Limit:	Not available.
Upper Flammability/Explosive Limit:	Not available.
Vapor Pressure:	Not available.
Vapor Density:	Not available.
Relative Density/Specific Gravity:	2.7
Solubility:	Partial.
Partition coefficient: n-octanol/water:	Not available.
Auto-ignition Temperature:	Not available.
Decomposition Temperature:	Not available.
Viscosity:	Not available.
Oxidizing Properties:	Not available.
Explosive Properties:	Not available.

Section 10: STABILITY AND REACTIVITY

10.1 REACTIVITY

No dangerous reaction known under conditions of normal use.

10.2 CHEMICAL STABILITY

Stable under normal storage conditions. Keep dry in storage.

10.3 POSSIBILITY OF HAZARDOUS REACTIONS

No dangerous reaction known under conditions of normal use.

10.4 CONDITIONS TO AVOID

Heat. Incompatible materials. Moisture.



SAFETY DATA SHEET

10.5 INCOMPATIBLE MATERIALS

None known.

10.6 HAZARDOUS DECOMPOSITION PRODUCTS

May include, and are not limited to: oxides of carbon.

Section 11: TOXICOLOGICAL INFORMATION

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS

Likely Routes of Exposure: Skin contact, skin absorption, eye contact, inhalation, and ingestion.

Symptoms related to physical/chemical/toxicological characteristics:

Eye: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns in the presence of moisture.

Skin: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. May cause sensitization by skin contact.

Ingestion: May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

Inhalation: May cause respiratory tract irritation.

Acute Toxicity:

Ingredient	LC50	LD50
Silica, crystalline, quartz	Not available.	Oral 120 g/kg, rat (TD ₁₀)
Portland cement	Not available.	Not available.
Cement, alumina, chemicals	Not available.	Not available.
Calcium sulfate	Not available.	Oral > 3000 mg/kg, rat
Gypsum	Not available.	Not available.
Calcium carbonate	Not available.	Oral 6450 mg/kg, rat
Kaolin	Not available.	Not available.
Lithium carbonate	> 2.17 mg/L 4 h, rat	Oral 525 mg/kg, rat

Calculated overall Chemical Acute Toxicity Values

LC50 (inhalation)	LD50 (oral)	LD50 (dermal)
Not available.	>2000 mg/kg, rat	Not available.

Ingredient	Chemical Listed as Carcinogen or Potential Carcinogen (NTP, IARC, OSHA, ACGIH, CP65)*
Silica, crystalline, quartz	G-A2, I-1, N-1, O, CP65
Portland cement	G-A4
Cement, alumina, chemicals	Not listed.
Calcium sulfate	Not listed.
Gypsum	Not listed.
Calcium carbonate	Not listed.
Kaolin	G-A4
Lithium carbonate	CP65



SAFETY DATA SHEET

* See Section 15 for more information.

11.2 DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT- AND LONG-TERM EXPOSURE

Skin Corrosion/Irritation:	Causes skin irritation.
Serious Eye Damage/Irritation:	Causes serious eye damage.
Respiratory Sensitization:	Based on available data, the classification criteria are not met.
Skin Sensitization:	May cause an allergic skin reaction.
STOT-Single Exposure:	May cause respiratory irritation.
Chronic Health Effects:	
Carcinogenicity:	May cause cancer.
Germ Cell Mutagenicity:	Based on available data, the classification criteria are not met.
Reproductive Toxicity:	
Developmental:	May damage the unborn child.
Teratogenicity:	Based on available data, the classification criteria are not met.
Embryotoxicity:	Based on available data, the classification criteria are not met.
Fertility:	May damage fertility.
STOT-Repeated Exposure:	Causes damage to lungs through prolonged or repeated exposure.
Aspiration Hazard:	Based on available data, the classification criteria are not met.
Toxicologically Synergistic Materials:	Not available.
Other Information:	Not available.

Section 12: ECOLOGICAL INFORMATION

12.1 ECOTOXICITY

Acute/Chronic Toxicity: May cause long-term adverse effects in the aquatic environment.

12.2 PERSISTENCE AND DEGRADABILITY

Not available.

12.3 BIOACCUMULATIVE POTENTIAL

Bioaccumulation: Not available.

12.4 MOBILITY IN SOIL

Not available.

12.5 OTHER ADVERSE EFFECTS

Not available.



SAFETY DATA SHEET

Section 13: DISPOSAL CONSIDERATIONS

13.1 WASTE TREATMENT METHODS

Disposal Method: This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

Other disposal recommendations: Not available.

Section 14: TRANSPORT INFORMATION

14.1 UN NUMBER

DOT

Not regulated.

TDG

Not regulated.

14.2 UN PROPER SHIPPING NAME

DOT

Not applicable.

TDG

Not applicable.

14.3 TRANSPORT HAZARD CLASS (ES)

DOT

Not applicable.

TDG

Not applicable.

14.4 PACKING GROUP

DOT

Not applicable.

TDG

Not applicable.

14.5 ENVIRONMENTAL HAZARDS

Not available.

14.6 TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE

Not available.

14.7 SPECIAL PRECAUTIONS FOR USER

Do not handle until all safety precautions have been read and understood.

Section 15: REGULATORY INFORMATION

15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/ LEGISLATIONS SPECIFIC FOR THE CHEMICAL

Canada: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

US: MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012



SAFETY DATA SHEET

SARA Title III				
Ingredient	Section 302 (EHS) TPQ (lbs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313
Silica, crystalline, quartz	Not listed.	Not listed.	Not listed.	Not listed.
Portland cement	Not listed.	Not listed.	Not listed.	Not listed.
Cement, alumina, chemicals	Not listed.	Not listed.	Not listed.	Not listed.
Calcium sulfate	Not listed.	Not listed.	Not listed.	Not listed.
Gypsum	Not listed.	Not listed.	Not listed.	Not listed.
Calcium carbonate	Not listed.	Not listed.	Not listed.	Not listed.
Kaolin	Not listed.	Not listed.	Not listed.	Not listed.
Lithium carbonate	Not listed.	Not listed.	Not listed.	313

State Regulations

California Proposition 65:

This product contains chemicals known to the State of California to cause birth defects or other reproductive harm. (Silica, crystalline; Lithium carbonate; Acetaldehyde; Methanol; Vinyl chloride)

Global Inventories:

Ingredient	Canada DSL/NDSL	USA TSCA
Silica, crystalline, quartz	DSL	Yes.
Portland cement	DSL	Yes.
Cement, alumina, chemicals	DSL	Yes.
Calcium sulfate	DSL	Yes.
Gypsum	DSL	Yes.
Calcium carbonate	NDSL	Yes.
Kaolin	DSL	Yes.
Lithium carbonate	DSL	Yes.

NFPA National Fire Protection Association:

Health:	2
Fire:	0
Reactivity:	0

HMIS-Hazardous Materials Identification System

Health:	2*
Fire:	0
Physical Hazard:	0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

- CP65** **California Proposition 65**
- OSHA (O)** **Occupational Safety and Health Administration.**
- ACGIH (G)** **American Conference of Governmental Industrial Hygienists.**
 A1 - Confirmed human carcinogen.
 A2 - Suspected human carcinogen.
 A3 - Animal carcinogen.
 A4 - Not classifiable as a human carcinogen.
 A5 - Not suspected as a human carcinogen.



SAFETY DATA SHEET

IARC (I) International Agency for Research on Cancer.

1 - The agent (mixture) is carcinogenic to humans.
2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.

2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.

3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.

4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

NTP (N) National Toxicology Program.

1 - Known to be carcinogens.
2 - Reasonably anticipated to be carcinogens.

Section 16: OTHER INFORMATION

Date of Preparation: January 3, 2014

Version: 1.0

Revision Date: January 3, 2014

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Prepared by: Nexreg Compliance Inc.
Phone: (519) 488-5126
www.nexreg.com

Prepared for: Custom Building Products

End of Safety Data Sheet