

**SOLARTRON ELECTRONICS INC -- STATNUL;ANTISTATIC AND CLEANER COMPOUND --
6850-00-882-6690**

===== Product Identification =====

Product ID:STATNUL;ANTISTATIC AND CLEANER COMPOUND

MSDS Date:04/07/1986

FSC:6850

NIIN:00-882-6690

MSDS Number: BFTTF

=== Responsible Party ===

Company Name:SOLARTRON ELECTRONICS INC

Address:614 FRELINGHUYSEN AVE

City:NEWARK

State:NJ

ZIP:07114-1324

Country:US

Info Phone Num:201-242-2600 (EXT.351)

Emergency Phone Num:201-242-2600 (EXT.238)

Preparer's Name:JOSEPH BEBEL

CAGE:65092

=== Contractor Identification ===

Company Name:INLAND PACKAGING INC

Address:209 PETERSON DR

Box:644

City:ELIZABETHTOWN

State:KY

ZIP:42701-9804

Country:US

Phone:502-737-6757

CAGE:66172

Company Name:SOLARTRON ELECTRONICS INC

Address:614 FRELINGHUYSEN AVE

Box:City:NEWARK

State:NJ

ZIP:07114-1324

Country:US

CAGE:65092

===== Composition/Information on Ingredients =====

Ingred Name:N-PROPYL ALCOHOL

CAS:71-23-8

RTECS #:UH8225000

Fraction by Wt: 24.0%

OSHA PEL:200 PPM

ACGIH TLV:S,200PPM/250STEL; 95

Ingred Name:SYNTHETIC ORGANIC SOAP

Fraction by Wt: 3.0%

Ingred Name:OTHER COMPONENTS (NOT SPECIFIED)

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE:IRRITATION OF EYES,SKIN AND
RESPIRATORY TRACT;HEADACHE, DIZZINESS, CNS

DEPRESSION.NAUSEA,VOMITING. CHRONIC:IRRITATION,EYE INJURY POSSIBLE.
 Explanation of Carcinogenicity:DATA PER MSDS
 Effects of Overexposure:EXCESSIVE VAPOR CAN CAUSE IRRITA,HEADACHE,
 DIZZINESS,MENTAL DEPRESSION,VOMITING,ANESTHESIA.
 Medical Cond Aggravated by Exposure:NO DATA AVAILABLE.

=====
 First Aid Measures
 =====

First Aid:INHALATION:REMOVE TO FRESH AIR. RESUSCITATE IF NOT BREATHING.
 GET MEDICAL ATTENTION. EYES:IMMEDIATELY FLUSH WITH PLENTY OF WATER
 FOR 15 MINUTES HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. SKIN:
 REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. IF
 IRRITATION PERSISTS, GET MEDICAL ADVICE. INGESTION:DO NOT INDUCE
 VOMITING. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. GET IMMEDIATE
 MEDICAL ATTENTION.

=====
 Fire Fighting Measures
 =====

Flash Point:85.0F,29.4C
 Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER
 FOG.
 Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &
 FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER
 SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.
 Unusual Fire/Explosion Hazard:CAN REACT VIGOROUSLY WITH OXIDIZING
 MATERIAL.

=====
 Accidental Release Measures
 =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;CONTAIN FREE
 MATERIAL IF POSSIBLE;USE SUITABLE INERT ABSORBENT MATERIAL AND
 RECOVER FOR PROPER DISPOSAL IN AN APPROVED CONTAINER.
 Neutralizing Agent:NOT APPLICABLE.

=====
 Handling and Storage
 =====

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED
 AREA. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE.
 Other Precautions:DO NOT TAKE INTERNALLY. DO NOT BREATHE MIST. AVOID
 PROLONGED OR REPEATED BREATHING OF VAPOR. AVOID CONTACT WITH EYES.
 USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING.

=====
 Exposure Controls/Personal Protection
 =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC
 VAPORS/MIST IF ABOVE TLV/PEL.
 Ventilation:LOCAL/GENERAL TO MAINTAIN PEL/TLV.
 Protective Gloves:IMPERVIOUS OR AS REQUIRED.
 Eye Protection:SAFETY GOGGLES WITH OPTIONAL FACE SHIELD
 Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER,WORK
 CLOTHING AND APRON AS REQUIRED.
 Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND
 RECOMMENDED PROCEDURES.
 Supplemental Safety and Health
 AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO
 NOT BREATHE VAPORS OR MISTS.

=====
 Physical/Chemical Properties
 =====

HCC:F3

Boiling Pt:=83.3C, 182.F
Melt/Freeze Pt:=-6.7C, 20.F
Vapor Pres:46 MMHG
Vapor Density:1.007
Spec Gravity:0.964-0.967
Evaporation Rate & Reference:2.4(N-BUTYL ACETATE = 1)
Solubility in Water:INFINITE
Appearance and Odor:WATER-WHITE CLEAR-ODOR SIMILAR TO RUBBING ALCOHOL.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
DO NOT APPLY TO THERMOPLASTICS WHILE UNDER EXTREME TEN.STRSS
Stability Condition to Avoid:PROLONGED CONTACT WITH CORRODABLE ALLOYS,
SUCH AS STEEL.
Hazardous Decomposition Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:CONSULT LOCAL AUTHORITIES.DISPOSAL MUST BE MADE
IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.